PUB-NO: JP02005179851A

DOCUMENT-IDENTIFIER: JF 2005179851 A

TITLE: RUBBER REINFORCING CORD MADE OF FOLYBENZANOLE FIBER

FUBN-DATE: July 7, 2005

INVENTOR-INFORMATION:

NAMic

COUNTRY KIRIYAMA, KOHEL MURASE, HIROTAKA

ABE, YUKIHIRO

INT-CL (IEC): D02G 3748; D01E 6794; B60C 9700

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a rubber-reinforcing cord made of a twisted polyber access fiber having small strength lowering even by exposing to a hightemperature and humidity atmosphere for a long period.

SOLUTION: A polybenzatole fiber having a strength retention of \geqslant 80% after the treatment in an atmosphere of 80°C and 80% relative humidity for 240 hrs in a state (wisted at a twist coefficient of 30 is produced by incorporating a yarn with an organic pigment having high heat-resistance represented by the thermal decomposition temperature of ≥200°C and soluble in a mineral acid, preferably containing -N= and/or NH- group in the molecular structure, especially perinones and/or perylenes, phthalocyanines or quinacridones. The rubber-reinforcing word is produced by using the polyben-azole fiber at least as a part of the cord.

COPYRIGHT: (C) 2005, JPO&NCIPI